

Logistics Report

for a

**DETAILED AIRBORNE
MAGNETIC, RADIOMETRIC AND
DIGITAL TERRAIN SURVEY**


for the

FOG BAY PROJECT

carried out on behalf of

HAPSBURG EXPLORATION PTY LTD

by



(UTS Job #A931)

FAUNTLEROY AVENUE, PERTH AIRPORT
PO BOX 126, BELMONT WA 6984
Telephone +61 8 9479 4232 Facsimile +61 8 9479 7361
A.B.N. 31 058 054 603

TABLE OF CONTENTS

1	GENERAL SURVEY INFORMATION.....	3
2	SURVEY SPECIFICATIONS.....	3
3	AIRCRAFT AND SURVEY EQUIPMENT.....	4
3.1	SURVEY AIRCRAFT.....	5
3.2	DATA POSITIONING AND FLIGHT NAVIGATION.....	5
3.3	UTS DATA ACQUISITION SYSTEM AND DIGITAL RECORDING.....	6
3.4	ALTITUDE READINGS.....	6
3.5	UTS STINGER MOUNTED MAGNETOMETER SYSTEM.....	6
3.6	TOTAL FIELD MAGNETOMETER.....	7
3.7	THREE COMPONENT VECTOR MAGNETOMETER.....	7
3.8	AIRCRAFT MAGNETIC COMPENSATION.....	7
3.9	DIURNAL MONITORING MAGNETOMETER.....	8
3.10	BAROMETRIC ALTITUDE.....	8
3.11	TEMPERATURE AND HUMIDITY.....	9
3.12	RADIOMETRIC DATA ACQUISITION.....	9
4	PROJECT MANAGEMENT.....	10
5	DATA PROCESSING PROCEDURES.....	11
5.1	DATA PRE-PROCESSING.....	11
5.2	MAGNETIC DATA PROCESSING.....	12
5.3	RADIOMETRIC DATA PROCESSING.....	13
5.4	DIGITAL TERRAIN MODEL DATA PROCESSING.....	13
	APPENDIX A - LOCATED DATA FORMATS.....	15
	APPENDIX B - COORDINATE SYSTEM DETAILS.....	17
	APPENDIX C - SURVEY BOUNDARY DETAILS.....	18
	APPENDIX D - PROJECT DATA OVERVIEW.....	19
	APPENDIX E – ACQUISITION AND PROCESSING PARAMETERS.....	20

1 GENERAL SURVEY INFORMATION

UTS Geophysics conducted a low level airborne geophysical survey for the following company:

Hapsburg Exploration PTY LTD
54 Tenth Street, Mildura
Victoria VIC 3500

Acquisition for this survey commenced on the 28th December 2007 and was completed on the 01st January 2008. The base location used for operating the aircraft and performing in-field quality control was Batchelor, Victoria.

2 SURVEY SPECIFICATIONS

The area surveyed was approximately 82km southeast of Batchelor in Victoria. The survey was flown using the MGA94 coordinate system (a Universal Transverse Mercator projection) derived from the Geocentric Datum of Australia and was contained within zone 52 with a central meridian of 129 degrees. Details of the datum and projection system are provided in Appendix B of this report. Survey boundary coordinates are listed in Appendix C.

The survey data acquisition specifications for each area flown are specified in the following table:

PROJECT NAME	LINE SPACING	LINE DIRECTION	TIE LINE SPACING	TIE LINE DIRECTION	SENSOR HEIGHT	TOTAL LINE KM
Fog Bay	100m	090-270	1000m	000-180	50m	2,210
TOTAL						2,210

The specified sensor height for the magnetic samples is as stated in the above table. This sensor height may be varied where topographic relief or laws pertaining to built up areas do not allow this altitude to be maintained, or where the safety of the aircraft and equipment is endangered.

3 AIRCRAFT AND SURVEY EQUIPMENT

The UTS navigation flight control computer, data acquisition system and geophysical sensors were installed into a specialised geophysical survey aircraft.

The list of geophysical and navigation equipment used for the survey is as follows:

General Survey Equipment

- FU24 – 954 fixed wing survey aircraft.
- UTS proprietary flight planning and survey navigation system.
- UTS proprietary high speed digital data acquisition system.
- Novatel 3951R, 12 channel precision navigation GPS.
- OMNILITE 132 real time differential GPS system.
- UTS LCD pilot navigation display and external track guidance display.
- UTS post mission data verification and processing system.
- Bendix King KRA-405 radar altimeter.

Magnetic Data Acquisition Equipment

- UTS tail stinger magnetometer installation.
- Scintrex Cesium Vapour CS-2 total field magnetometer.
- Fluxgate three component vector magnetometer.
- RMS Aeromagnetic Automatic Digital Compensator (AADC II).
- Diurnal monitoring magnetometer (Scintrex Envimag).

Radiometric Data Acquisition Equipment

- Exploranium GR-820 gamma ray spectrometer.
- Exploranium gamma ray detectors.
- Barometric altimeter (height and pressure measurements).
- Temperature and humidity sensor.

3.1 **Survey Aircraft**

The aircraft used for this survey was a FU24 – 950 series fixed wing survey aircraft, owned and operated by UTS Geophysics, registration VH-HVP. The specifications are as follows:

Power Plant

- Engine Type Single engine, Lycoming, IO-720
- Brake Horse Power 400 bhp
- Fuel Type AV-GAS

Performance

- Cruise speed 105 Kn
- Survey speed 100 Kn
- Stall speed 45 Kn
- Range 970 Km
- Endurance (no reserves) 5.6 hours
- Fuel tank capacity 490 litres



3.2 **Data Positioning and Flight Navigation**

Survey data positioning and flight line navigation was derived using real-time differential GPS (Global Positioning System).

Navigation was performed using a UTS designed and built electronic pilot navigation system providing computer controlled digital navigation instrumentation mounted in the cockpit as well as an externally mounted track guidance system.

GPS derived positions were used to provide both aircraft navigation and survey data location information.

The GPS systems used for the survey were:

- Aircraft GPS Model Novatel 3951R
- Sample rate 0.5 Seconds (2 Hz)
- GPS satellite tracking channels 12 parallel
- Typical differentially corrected accuracy 1-2 metres (horizontal)
3-5 metres (vertical)

3.3 *UTS Data Acquisition System and Digital Recording*

All geophysical sensor data and positional information measured during the survey was recorded using a UTS developed, high speed, precision data acquisition system. Survey data was downloaded onto magnetic tape on completion of each survey flight.

Instrument synchronisation times were measured and removed in real-time by the UTS data acquisition system.

3.4 *Altitude Readings*

Accurate survey heights above the terrain were measured using a King radar altimeter installed in the aircraft. The height of each survey data point was measured by the radar altimeter and stored by the UTS data acquisition system.

- Radar altimeter models King KRA- 405 twin antenna altimeter
- Accuracy 0.3 metres
- Resolution 0.1 metres
- Range 0 - 500 metres
- Sample rate 0.1 Seconds (10Hz)

The digital terrain model is calculated by subtracting the terrain clearance (radar altimeter) from the GPS height (interpolated to 0.1 Hz), and as such the accuracy is constrained by the differentially corrected GPS position.

3.5 *UTS Stinger Mounted Magnetometer System*

The installation platform used for the acquisition of magnetic data was a tail mounted stinger. This proprietary stinger system was constructed of carbon fibre and designed for maximum rigidity and stability.

Both the total field magnetometer and three component vector magnetometer were located within the tail stinger.



3.6 **Total Field Magnetometer**

Total field magnetic data readings for the survey were made using a Scintrex Cesium Vapour CS-2 Magnetometer. This precision sensor has the following specifications:



- Model Scintrex Cesium Vapour CS-2 Magnetometer
- Sample Rate 0.1 seconds (10Hz)
- Resolution 0.001nT
- Operating Range 15,000nT to 100,000nT

3.7 **Three Component Vector Magnetometer**

Three component vector magnetic data readings for the survey were made using a Develco Fluxgate Magnetometer. This precision sensor has the following specifications:

- Model Develco Fluxgate Magnetometer
- Sample Rate 0.1 seconds (10Hz)
- Resolution 0.1nT
- Operating Range -100,000nT to 100,000nT

3.8 **Aircraft Magnetic Compensation**

At the start of the survey, the system was calibrated for reduction of magnetic heading error. The heading and manoeuvre effects of the aircraft on the magnetic data was removed using an RMS Automatic Airborne Digital Compensator (AADC II).

Calibration of the aircraft heading effects were measured by flying a series of pitch, roll and yaw manoeuvres at high altitude while monitoring changes in the three axis magnetometer and the effect on total field readings. A 26 term model of the aircraft magnetic noise covering permanent, induced and eddy current fields was determined. These coefficients were then applied to the data collected during the survey in real-time.

UTS static compensation techniques were also employed to reduce the initial magnetic effects of the aircraft upon the survey data.

3.9 Diurnal Monitoring Magnetometer

A base station magnetometer was located in a low gradient area beyond the region of influence of any man made interference to monitor diurnal variations during the survey.

The specifications for the magnetometer used are as follows:

- Model Scintrex Envimag
- Resolution 0.1 nT
- Sample interval 5 seconds (0.2 Hz)
- Operating range 20,000nT to 90,000nT
- Temperature -20°C to +50°C



3.10 Barometric Altitude

An Air DB barometric altimeter was installed in the aircraft so as to record and monitor barometric height and pressure. The data was recorded at 0.10 second intervals and is used for the reduction of the radiometric data.

- Model Air DB barometric altimeter
- Accuracy 2 metres
- Height resolution 0.1 metres
- Height range 0 - 3500 metres
- Maximum operating pressure: 1,300 mb
- Pressure resolution: 0.01 mb
- Sample rate 10 Hz

3.11 *Temperature and Humidity*

Temperature and humidity measurements were made during the survey at a sample rate of 10Hz. Ambient temperature was measured with a resolution of 0.1 degree Celsius and ambient humidity to a resolution of 0.1 percent.

3.12 *Radiometric Data Acquisition*

The gamma ray spectrometer used for the survey was capable of recording 256 channels and was self stabilising in order to minimise spectral drift. The detectors used contain thallium activated sodium iodide crystals.

Thorium source measurements were made each survey day to monitor system resolution and sensitivity. A calibration line was also flown at the start and end of each survey day to monitor ground moisture levels and system performance.

Spectrometer model	Exploranium GR820
• Detector volume	32 litres
• Sample rate	1 Hz



4 PROJECT MANAGEMENT

Hapsburg Exploration PTY LTD

Mohan Varkey

UTS Geophysics Perth Office

Nino Tuffili
David Abbott
Cameron Johnston
Rebecca Steadman

5 DATA PROCESSING PROCEDURES

5.1 *Data Pre-processing*

The raw survey data was loaded from the field tapes and the recorded data trimmed to the correct survey boundary extents. Any survey lines subsequently re flown were removed from the dataset.

At the commencement of each acquisition flight, all the instrumentation clocks were synchronized to local time, and the error and latency of each instrument in providing its data measurement calculated. The results of these latency measurements were recorded into a synchronisation file, and the results used to assign GPS positions to the magnetic, radiometric and elevation data. As a result of the physical separation of the sensors, a small residual offset still exists between instrument timings.

To compensate for this residual parallax error, an adjustment was made to the instrument clocks. The magnetic and radar altimeter data was adjusted by 0.600 seconds, and the radiometric data was adjusted by 1.375 seconds for each flight.

The synchronized, parallax corrected data was then exported as located ASCII data.

5.2 Magnetic Data Processing

The diurnal base station data was checked for spikes and steps, and suitably filtered prior to the removal of diurnal variations from the aircraft magnetic data.

The filtered diurnal measurements were subtracted from the diurnal base field and the residual corrections applied to the survey data by synchronising the diurnal data time and the aircraft survey time. The average diurnal base station value was added to the survey data.

The X and Y positioning of the data was then checked for spikes before applying the IGRF correction. Any spikes in the positions were manually edited. The updated IGRF 2005 correction was calculated at each data point (taking into account the height above sea level).

This regional magnetic gradient was subtracted from the survey data points.

Tie line levelling was applied to the data by least squares minimisation, using a polynomial fit of order 0, of the differences in magnetic values at the crossover points of the survey traverse and tie line data.

In order to remove any residual long wavelength variations in the tie line levelled data along the traverse lines, polynomial levelling was then applied.

Final micro-levelling techniques were then selectively applied to the tie line levelled data to remove minor residual variations in profile intensity

Located and gridded data were generated from the final processed magnetic data.

5.3 Radiometric Data Processing

Statistical noise reduction of the 256 channel data was performed using the Noise Adjusted Singular Variable Decomposition (NASVD) method described by Hovgaard and Grasty (1997).

Noise-adjusted singular value decomposition is performed, and the number of components to be used is determined by inspection of plots of the spectral components and by a statistical analysis of the contributions of the components. If the spectral shapes show any unusual characteristics, further analysis of the concentrations of the spectral components in the line data is performed in order to identify and eliminate any corrupt spectra. If such spectra were eliminated, the NASVD process is re-performed, in order to obtain spectral components free of any bias from corrupt spectra.

Only the dominant spectral shapes (identified as described above) were used in the spectral reconstruction process. The first 10 NASVD components were used for this process.

Channels 30-250 only are spectrally smoothed, as these contain the regions of interest and are not dominated by the lower end of the Compton continuum. The energy spectrum between the potassium and thorium peaks was recalibrated from the spectrally smoothed 256 channel measurements.

The aircraft background spectrum and the scaled unit cosmic spectrum were then subtracted from the 256 channel data. This 256 channel data was then windowed to the 5 primary channels of total count, potassium, uranium, thorium and low-energy uranium. Dead time corrections were then applied to the data. Radon background removal was performed using the Minty Spectral Ratio method (1992).

The radar altimeter data was corrected to standard temperature and pressure, and height corrected spectral stripping was then applied to the windowed data. Height attenuation corrections based on the STP radar altimeter were then performed to remove any altitude variation effects from the data.

The Uranium and Total Count channels were tie-levelled to remove the effects of residual radon background. The tie-levelling process employed was a least-squares/median filter procedure, which generated a single correction for each line of data. Mis-matches were calculated at each tie-traverse intersection and the median mismatch for each flight line was calculated as the residual levelling error for that line.

Final micro-levelling techniques were then selectively applied to the tie line levelled data to remove minor residual variations in profile intensities, as per the method outlined for magnetic data micro-levelling in 7.2 above. Limits were applied to the radiometric channels in selected areas only during the micro-levelling process are shown in the table below.

5.4 Digital Terrain Model Data Processing

The radar altimeter data was subtracted from the GPS altimeter data. The separation distance between the GPS antenna and the radar altimeter of 1.4 metres was subtracted from the digital terrain data.

The digital terrain data thus derived was tie line levelled and gridded. Tie line levelled data was then examined and selectively microlevelled to produce a grid without line dependent artifacts.

For further information concerning the survey flown, please contact the following office:

Head Office Address:

UTS Geophysics
Fauntleroy Avenue, Perth Airport
REDCLIFFE WA 6104

Tel: +61 8 9479 4232
Fax: +61 8 9479 7361

Postal Address:

UTS Geophysics
P.O. Box 126
BELMONT WA 6984

Quoting reference number: A931

APPENDIX A - LOCATED DATA FORMATS

MAGNETIC LOCATED DATA

FIELD	FORMAT	DESCRIPTION	UNITS
1	I8	LINE NUMBER	
2	I4	FLIGHT/AREA NUMBER	AAFF (Area/Flight)
3	I9	DATE	YYMMDD
4	F10.1	TIME	sec
5	I8	FIDUCIAL NUMBER	
6	I4	UTM ZONE	
7	F12.6	LATITUDE (WGS84)	degrees
8	F12.6	LONGITUDE (WGS84)	degrees
9	F12.2	EASTING (MGA94)	metres
10	F12.2	NORTHING (MGA94)	metres
11	F8.1	RADAR ALTIMETER HEIGHT	metres
12	F8.1	GPS HEIGHT (WGS84)	metres
13	F8.1	TERRAIN HEIGHT (WGS84)	metres
14	F10.2	RAW MAGNETIC INTENSITY	nT
15	F10.2	DIURNAL CORRECTION	nT
16	F10.2	IGRF CORRECTION	nT
17	F10.2	DRN AND IGRF CORRECTED TMI	nT
18	F10.2	FINAL TOTAL MAGNETIC INTENSITY	nT

RADIOMETRIC LOCATED DATA

FIELD	FORMAT	DESCRIPTION	UNITS
1	I8	LINE NUMBER	
2	I4	FLIGHT/AREA NUMBER	AAFF (Area/Flight)
3	I9	DATE	YYMMDD
4	F10.1	TIME	sec
5	I8	FIDUCIAL NUMBER	
6	I4	UTM ZONE	
7	F12.6	LATITUDE (WGS84)	degrees
8	F12.6	LONGITUDE (WGS84)	degrees
9	F12.2	EASTING (MGA94)	metres
10	F12.2	NORTHING (MGA94)	metres
11	F8.1	RADAR ALTIMETER HEIGHT	metres
12	F8.1	GPS HEIGHT (WGS84)	metres
13	I5	LIVE TIME	milli sec
14	F8.1	PRESSURE	hPa
15	F6.1	TEMPERATURE	Degrees Celcius
16	F6.1	HUMIDITY	percent
17	I6	TOTAL COUNT (RAW)	Counts/sec
18	I6	POTASSIUM (RAW)	Counts/sec
19	I6	URANIUM (RAW)	Counts/sec
20	I6	THORIUM (RAW)	Counts/sec
21	I6	COSMIC (RAW)	Counts/sec
22	F8.1	TOTAL COUNT (CORRECTED)	Counts/sec
23	F8.1	POTASSIUM (CORRECTED)	Counts/sec
24	F8.1	URANIUM (CORRECTED)	Counts/sec
25	F8.1	THORIUM (CORRECTED)	Counts/sec
26	F9.4	DOSE RATE	nGy/hr
27	F9.4	POTASSIUM GRND CONCENTRATION	%
28	F9.4	URANIUM GRND CONCENTRATION	ppm
29	F9.4	THORIUM GRND CONCENTRATION	ppm

GRIDDED DATASET FORMATS

Gridding was performed using a bicubic spline algorithm.

The following grid formats have been provided:

- ER-Mapper format

LINE NUMBER FORMATS

Line numbers are identified with a six digit composite line number and have the following format - ALLLLB, where:

A	Survey area number
LLLL	Survey line number 0001-8999 reserved for traverse lines 9001-9999 reserved for tie lines
B	Line attempt number, 0 is attempt 1, 1 is attempt 2 etc..

UTS FILE NAMING FORMATS

Located and gridded data provided by UTS Geophysics uses the following 8 character file naming convention to be compatible with PC DOS based systems.

File names have the following general format - JJJJAABB.EEE, where:

JJJJ	UTS Job number
AA	Area number if the survey is broken into blocks
BB	M Magnetic data R Radiometric data TC Total count data K Potassium counts U Uranium counts Th Thorium counts DT Digital terrain data
EEE	File name extension LDT Located digital data file FMT Located data format definition file ERS Ermapper gridded data header file Ermapper data portion has no extension GRD Geosoft gridded data file

APPENDIX B - COORDINATE SYSTEM DETAILS

Locations for the survey data are provided in both geographical latitude and longitude and Universal Transverse Mercator metric projection coordinate systems.

WGS84	World Geodetic System 1984
Coordinate Type	Geographical
Semi Major Axis	6378137m
Flattening	1/298.257223563
MGA94	Map Grid of Australia 1994
Coordinate type	Universal Transverse Mercator Projection Grid
Geodetic datum	Geocentric Datum of Australia
Semi major axis	6378137m
Flattening	1/298.257222101

APPENDIX C - SURVEY BOUNDARY DETAILS

COORDINATES REPORT

Job ID code: A93101t1
Client: Hapsburg Exploration
Job: Fog Bay
Grid Zone: 52
Include Point: 0.0 0.00

Surround

646700.000	8588400.000
657500.000	8588400.000
657500.000	8571600.000
644600.000	8571600.000
644600.000	8575600.000
646700.000	8581800.000
646700.000	8588400.000

APPENDIX D - PROJECT DATA OVERVIEW

Fog Bay Project

Total Magnetic Intensity

Radiometric Total Count

Digital Terrain Model

APPENDIX E – ACQUISITION AND PROCESSING PARAMETERS

Magnetic Processing Parameters

Model : IGRF 2007.99
 Average Declination : 3.49 degrees
 Average Inclination : -40.56 degrees
 Average Field strength: 46738.39 nT
 Average diurnal : 46.380 nT

Radiometric Processing Parameters

Height Attenuation Coefficients

Total Count: -0.0074
 Potassium: -0.0094
 Uranium: -0.0084
 Thorium: -0.0074

Cosmic Correction Coefficients

Total Count: 1.051
 Potassium: 0.047
 Uranium: 0.046
 Thorium: 0.055

Aircraft Background Coefficients

Total Count: 62.96
 Potassium: 8.34
 Uranium: 2.57
 Thorium: 1.11

Sensitivity Coefficients

Total Count: 38.95cps/dose rate
 Potassium: 183.985 cps/%k
 Uranium: 16.337 cps/ppm
 Thorium: 7.792cps/ppm

Final Reduction - All data reduced to STP height datum 30m