

WELL	SIMPSON-1
RIG	HUNT RIG 2
SPUDDED	12:30 1/10/2008
DAYS SINCE SPUD	15.5
LAST CASING	9-5/8" at 795m
LAST BOP TEST	7-Oct-08



CP-301

DAILY DRILLING REPORT

REPORT DATE:	17-Oct-08
REPORT NO.	16
MIDNIGHT DEPTH m :	2093
PREVIOUS DEPTH m :	2077
PROGRESS m :	16

2400 - 0600 UPDATE : Drill from 2093m to 2102m

FORWARD PLAN	:	Continue drilling 8-1/2" hole
--------------	---	-------------------------------

BIT PERFORMANCE			MUD PROPERTIES		ADDITIVES	PUMP DATA		1	2
Bit Number	4	5	Weight ppg/SG	9.1 / 1.09	3 Pac R	Type	TSM 500	Emsco 550	
Size	8.5	8.5	Vis	37	1 Biocide	Bore x Stroke	5 1/2 x 16	5 1/2 x 16	
Serial No	NR2430	M12910	API WL	8.4	64 KCL	SPM		60	
Manufacturer	Stealth	Stealth	FC	1	2 Soda ash	GPM @ 95% n		336	
Type	JTC51	JTC61	PV/YP	10 / 16	23 Baryte	Pressure		1350	
IADC Code	517	617	Gels	6 / 10	1 Caustic	SPR SPM	42	44	
Jets	2 x 13, 1 x 12	3 x 12	% Solids	4.5		SPR Pressure	500	500	
Depth In	1923	2077	% Sand	0.10		FUEL	USED	ON-SITE	
Depth Out	2077		MBC ppb	7.5		RIG	2650	31890	
Drilled	154	16	pH	9.1		CAMP	200	2600	
Hours	28.5	10	Chloride	17000		PERSONNEL ON SITE			
ROP m/hr	5.4	1.6	Hardness	440		COMPANY		NO.	
WOB x 1000lb	35	30	F/line Temp °C	45		Central Petr.		2	
RPM	80	70	PHPA ppb	0.59		Hunt		20	
AV DP/DC fpm	159 / 248	159 / 248	KCL % by wt	2.9		BHI mud loggers		4	
J.V. fps	292	326	COSTS	MUD	WELL	RMN		1	
BIT HHP/sq in	2.40	2.99	Previous	\$40,380		KJM		1	
Condition	7,6,WT,A,E,1/16,BT,PR		Daily	\$2,684					
BHA No.	4	4	Cum	\$43,064					
BHA DETAILS: Bit, NB Stab, 6-1/2"DC, Stab, 2x6-1/2"DCs, Stab, 14x6-1/2" DCs, D/Jar, BHA #4									
SURVEYS:						TOTAL		28	

[illegible]