

APPENDIX 1DRILLING FLUID SUMMARYLAWRENCE-1

DATE	TIME	DEPTH (m)	WT (ppg)	FV (sec)	OPERATION	FORMATION	MUD USED *
22/9/88	1430	00.0		60	Coring	Velkerri Fm.	Liquid poly A,B,C
23/9/88	0900	10.15	8.5	47	"		
	1200		8.5	49	"		
	1530		8.5	42	"		
	1700	19.4	8.5	34	"		
	2400		8.5	36	"		
24/9/88	0500		8.5	32	"		A,B,C
	0700	35.1	8.6	30	"		
	1130		8.6	39	"		
	1530		8.6	35	"		
	1900	45.6	8.5	34	"		
	2400		8.5	36	Ream to 5 5/8"		
25/9/88	0730	57.5	8.5	35	Nipple up B.O.P		A,B,C
26/9/88	0330		8.5	31	Fit B.O.P. Test Coring		
	0600	65.5	8.4	28	Circulate & Condition Mud		
	0800		8.4	35	Coring		
	1530		8.4	48	"		
	1830	83.4	8.5	47	"		
	2400		8.5	52	Coring		
27/9/88	0500		8.5	48	"		
	0830	110.0	8.4	40	"		
	1330		8.4	39	"		

DATE	TIME	DEPTH (m)	WT (ppg)	FV (sec)	OPERATION	FORMATION	MUD USED *		
28/9/88	1600	133.6	8.4	37	Coring	dropped core Dolerite Sill	A		
	1900		8.5	34	"				
	2400		8.5	50	"				
	0500	8.5	41	"					
	0730	165.2	8.4	41	"				
29/9/88	1300	194.0	8.4	40	Coring Ream over			Bessie Creek Sst A,B,C,4xHigh Seal, 1xMica	2xA 2xB 1xMica 3xliquid poly 6xHigh Seal
	1730		8.4	40	Coring				
	2100		8.4	40	"				
	0100	8.4	39	"					
	0400	8.4	39	"					
30/9/88	0700	220.2	8.4	38	"	Corcoran Form.	ABC 2xliquid		
	1130	8.4	36	"					
	1500	8.4	40	"					
	2100	251.7	8.4	40	"				
	0100	8.4	41	"					
1/10/88	0400	268.5	8.4	41	"			Corcoran Form.	ABC 2xliquid
	0700		8.4	37	"				
	1300		8.4	38	"				
	1030	282.6	8.4	38	"				
	2/10/88	1600	291.7	8.4	40				
2200		8.4		38	"				
0100		8.4		36	"				
0400		8.4	36	"					
0700		306.8	8.4	50	"				
	1200		8.4	50	"				

Appendix 1 Cont'd

DATE	TIME	DEPTH (m)	WT (ppg)	FV (sec)	OPERATION	FORMATION	MUD USED *
3/10/88	1700	329.8	8.4	50	Coring		AB 1xliquid p
	2000		8.4	38	"		
	0100		8.4	40	"		
4/10/88	0400	355.0	8.4	45	"		A2xB 1xliquid
	1000		8.4	40	"		
	1600		8.4	40	"		
5/10/88	1700		8.4	40	"		
	2100		8.4	40	"		
	0200		8.4	40	"		
6/10/88	1400		8.4	40	"		
	1700		8.4	32	"		
	0200		8.4	37	"		
	0500	364.8	8.4	35	"		A,B
	0600		8.4	28	"		
	1200		8.4	40	"		
8/10/88	1730	384.8	8.4	36	"		B
	1900		8.4	38	"		
	0000		8.4	35	"		
	0400	411.4	8.4	30	"		ABC 22xR Trol
	0830		8.4	34	"		
	1330		8.4	41	"		
8/10/88	2000	427.5	8.5	37	"		A,B
	0000		8.5	37	"		
	0400		8.5	35	Coring		
	1000	450.0	8.4	41	"		ABC 4xHigh Sl
	1400		8.4	37	"		
	1700		8.4	35	"		
9/10/88	2100	468.6	8.4	35	"	Abner Sst Munyi	2xA,C Member
	0100		8.4	37	"		
	0400		8.4	40	"		
	0700	492.8	8.4	40	"		
	1200		8.4	39	"		
	1600		8.4	37	"		
10/10/88	2000	506.5	8.4	35	"	Hodgson Sandstone	B,C
	0000		8.4	35	"		
	0400		8.4	36	"		
	0700	524.9	8.4	34	"		C
	1100		8.4	35	Condition & Circulate Hole		

* A = CMCLV (25kg), B = New Vis (20kg), C = New Drill (25)