



Santos Limited
GPO Box 2319
ADELAIDE SA 5000
Australia

Attention: Noel Dowdell

Project **08PEAD0018638**
Client Ref: 849485-101

Customer Sample ID	West Merreeie
	18
Sample Type	Gas
Date Sampled	31/05/2008
Time Sampled	1500h
Pressure	2497kPag
Temperature	32°C
Cylinder ID	JPE735
Test/Reference	Unit

Hydrotesting Cyl
Hydrotesting* Pass

GAS ANALYSIS
Test/Reference Unit

Gas Analysis ASTM D 1945-96 (modified)

Nitrogen	Mol %	9.63
Carbon Dioxide	Mol %	0.03
Methane	Mol %	70.14
Ethane	Mol %	12.36
Propane	Mol %	4.72
I-Butane	Mol %	0.51
N-Butane	Mol %	1.32
I-Pentane	Mol %	0.34
N-Pentane	Mol %	0.38
Hexanes	Mol %	0.30
Heptanes	Mol %	0.14
Octanes and higher hydrocarbons	Mol %	0.13
Total	Mol %	100.00

Gas Parameters ASTM D 1945-96 (modified)

Average Molecular Weight		21.89
Lower Flammability Limit		4.36
Upper Flammability Limit		15.39
Ratio Of Upper To Lower		3.53
Wobbe Index		50.01
Compressibility Factor (Z)		0.9969
Ideal Gas Density (Rel to Air = 1)		0.756
Real Gas Density (Rel to Air = 1)		0.758
Ideal Nett Calorific Value	MJ/m ³	39.46
Ideal Gross Calorific Value	MJ/m ³	43.48
Real Nett Calorific Value	MJ/m ³	39.58
Real Gross Calorific Value	MJ/m ³	43.62
Gross Calorific Val Water-Sat Gas	MJ/m ³	42.72

Test Description**Gas Parameters**

The above results are calculated on an air and water free basis assuming only the measured constituents are present. The following parameters are calculated from the above composition at 15°C and 101.325 kPa (abs) using ISO 6976 and the physical constants from the GPSA SI Engineering Data Handbook 11 th Ed.

Authorised By

Neil Thomas

Chemist

Michelle Fordham

Chemist

Accreditation No 2013

Laboratory Manager

Diane Cass

Operations Manager

**Final Report**

- Indicates Not Requested

* Indicates NATA accreditation does not cover the performance of this service

Samples will be discarded after 30 days unless otherwise notified.

Amdel Limited shall not be liable for loss, cost, damages or expenses incurred by the client, or any other person or company, resulting from the use of any information or interpretation given in this report. In no case shall Amdel Limited be liable for consequential damages including, but not limited to, lost profits, damages for failure to meet deadlines and lost production arising from this report. This document shall not be reproduced except in full and relates only to the items tested. Unless indicated otherwise, the tests were performed on the samples as received. *The samples were not collected by Amdel staff.*



NATIONAL HYDRO TESTING SERVICES

1 ELLEMSEA CCT. LONSDALE SA 5160
PH 8326 7755 MOBILE 0418 804 144

REGISTERED
MARK

REF # JPE 735

Date of Test:	8/08
Previous Test Date:	
Reference Temperature:	14
Service:	#

TESTED IN COMPLIANCE WITH AS2030.1

CERTIFICATE OF TEST

29600

S.A.A.
APPROVED

TEST STATION No.: 308A

Client:

AMDEL

Serial No.:

07EK096

Specification No.:

DOT 3E 180 0

Water Capacity:

0.5L

Test Pressure:

2925 PSI

Working Pressure:

1800 PSI

Condition: External

Condition: Internal

HYDROSTATIC/VISUAL TEST RESULT:

Passed

WEIGHT TEST: Passed

Good

Good

Recommendation or Remarks:

Average

Average

Poor

Poor

Approved Signatory: 