

This document is issued in accordance with NATA's accreditation requirements. Accredited for compliance with ISO/IEC 17025 Accreditation No 2013

Certificate of Analysis

Santos Limited GPO Box 2319 ADELAIDE SA 5000 Australia

## Attention: Noel Dowdell

Project	
Client Ref:	

**08PEAD0018640** 849485-101

Customer Sample ID		East Mereenie 43		
Sample Type		Gas		
Date Sampled		03/06/2008 1400 h		
Time Sampled Pressure Temperature		1400 m 1819 kPag 29°C		
Test/Reference	Unit			
Hydrotesting Cyl Hydrotesting*		Pass		
GAS ANALYSIS				
Test/Reference	Unit			
Gas Analysis ASTM D 1945-96 (modified)				
Nitrogen	Mol %	6.67		
Carbon Dioxide	Mol %	0.09		
Methane	Mol %	71.06		
Ethane	Mol %	13.53		
Propane	Mol %	5.15		
I-Butane	Mol %	0.52		
N-Butane	Mol %	1.47		
I-Pentane	Mol %	0.38		
N-Pentane	Mol %	0.46		
Hexanes	Mol %	0.39		
Heptanes	Mol %	0.19		
Octanes and higher hydrocarbons	Mol %	0.09		
Total	Mol %	100.00		
Gas Parameters ASTM D 1945-96 (modified)				
Average Molecular Weight		22.05		
Lower Flammability Limit		4.17		
Upper Flammability Limit		14.84		
Ratio Of Upper To Lower		3.56		
Wobbe Index		52.21		
Compressibility Factor (Z)		0.9966		
Ideal Gas Density (Rel to Air = 1)		0.761		
Real Gas Density (Rel to Air = 1)		0.763		
Ideal Nett Calorific Value	MJ/m <sup>3</sup>	41.35		
Ideal Gross Calorific Value	MJ/m <sup>3</sup>	45.55		
Real Nett Calorific Value	MJ/m <sup>3</sup>	41.49		
Real Gross Calorific Value	MJ/m³	45.71		
Gross Calorific Val Water-Sat Gas	MJ/m³	44.76		
Test Description				
Gas Parameters	only th	pove results are calculated on an air and water free basis assuming ne measured constituents are present. The following parameters are ated from the above composition at 15°C and 101.325 kPa (abs)		

calculated from the above composition at 15°C and 101.325 kPa (abs) using ISO 6976 and the physical constants from the GPSA SI Engineering Data Handbook 11 th Ed.



Authorised By Neil Thomas Michelle Fordham

Chemist Chemist

Accreditation No 2013

Laboratory Manager

Diane Cass

**Operations Manager** 

Rass

Final Report

- Indicates Not Requested

\* Indicates NATA accreditation does not cover the performance of this service

Samples will be discarded after 30 days unless otherwise notified.

Amdel Limited shall not be liable for loss, cost, damages or expenses incurred by the client, or any other person or company, resulting from the use of any information or interpretaton given in this report. In no case shall Amdel Limited be liable for consequential damages including, but not limited to, lost profits, damages for failure to meet deadlines and lost production arising from this report. This document shall not be reproduced except in full and relates only to the items tested. Unless indicated otherwise, the tests were performed on the samples as received. The samples were not collected by Amdel staff.

NATIONAL HYDRO TESTING				Date of Test: 8/08	
1 ELLEMSEA CCT. LONSDALE SA 5160 PH 8326 7755 MOBILE 0418 804 144				Previous Test Date: Reference Temperature:	
MARK # ANO 284	+ (EM43)		Servi	ce: T	
	ERTIFICA	TE OF TEST 29	587	S.A.A. APPROVED	
WITH AS2030.1				TEST STATION No.: 3084	
Client: AMDE	L	/ / / / / / / / / / / / / / / /	Serial No.:	AAO 284	
Specification No.:	DOT 3E-18	90			
Water Capacity:	·5L	Test Pressure: 2925 PS	Workin	Working Pressure: 1800 PS	
Condition: External	Condition: Internal	HYDROSTATIC/VISUAL TEST RESULT:		VEIGHT TEST: Passed	
Good	Good	Recommendation or Remarks:			
Average	Average				
Poor	Poor				