



Bit Summary

Amungee NW-1H

Job Type: DRILLING ORIGINAL

API / UWI	Surface Legal Location	License #	Well Configuration Type HORIZONTAL	Ground Elevation (m) 260.562	Casing Flange Elevation (m)	KB-Ground Distance (m) 5.36	KB-Casing Flange Distance (m)
-----------	------------------------	-----------	---------------------------------------	---------------------------------	-----------------------------	--------------------------------	-------------------------------

Bits

BHA #	Bit Run	Size (in)	Make	Model	SN	IADC Codes	TFA (in²)	Nozzles (1/32")	Depth In (mKB)	Depth Out (mKB)	Drilled (m)	Drill Time (hr)	BHA ROP (m/hr)	WOB Max (1000lbf)	WOB Min (1000lbf)	Max RPM (rpm)	Min RPM (rpm)	Bit Grading
1	1	6 3/4	Smith	MDSi713LWUBPX	JJ4558	713	0.91	13/13/13/13/13/13/13										0-0-NO-A-X-0-NO-BHA
2	2	6 3/4	Smith	XR50 ODPS	RD3412	627	0.75	18/18/18	1,932.5	1,932.5		19.00		15	1	160	156	0-0-NO-A-0-0-NO-BHA
3	3-1RR1	6 3/4	Smith	MDSi713LWUBPX	JJ4558	713	0.91	13/13/13/13/13/13/13	1,932.5	1,932.5		26.00		1	1	90	90	0-0-NO-A-X-0-NO-BHA
4	4-1RR2	6 3/4	Smith	MDSi713LWUBPX	JJ4558	713	0.91	13/13/13/13/13/13/13	1,932.5	2,798	865.5	127.79	6.8	15	8	154	154	1-1-WT-A-X-0-NO-BHA
5	5	6 3/4	Smith	MDSIR516	JJ3265	516	0.55	12/12/12/12/12	2,798	3,808	1,010	102.95	9.8	12	8	90	80	1-1-ER-A-X-0-NO-TD
6	6-1RR3	6 3/4	Smith	MDSi713LWUBPX	JJ4558	713	0.91	13/13/13/13/13/13/13	3,808	3,808								1-1-WT-A-X-0-NO-BHA
7	7-2RR1	6 3/4	Smith	XR50 ODPS	RD3412	627	0.75	18/18/18	3,808	3,808								0-0-PB-A-4-1-NO-TD