

Day	Depth (mMDRT)		Background Gas (%)	Chromatolog (ppm)			Max. Gas Peak (%)		Connecton Gas (%)		Trip Gas (%)		H2S (ppm)			CO2 (%)			Comment
	Start	End		C1	C2	C3	Depth	Gas	Depth	Gas	Depth	Gas	Min	Median	Max	Min	Median	Max	
1	17	36	0	0 - 8	0 - 4	0 - 2							0	0	0	0	0.01	0.06	
2	36	190	0	0 - 12	0 - 4	0 - 4							0	0	0	0	0	0.44	
3	190	205.7	0	0	0	0							0	0	0	0	0	0.01	16" Conductor Casing TD @ 205.7 mMDRT
4	205.7	205.7	0	0	0	0							0	0	0	0	0	0	
5	205.7	260	0	0 - 2	0 - 3	0 - 1							0	0	0	0	0	0.01	
6	260	327	0	0 - 8	0 - 6	0 - 5							0	0	0	0	0	0.26	
7	327	468	0	0 - 10	0 - 8	0 - 4							0	0	0	0	0	0.01	
8	468	514	0	0 - 13	0 - 8	0 - 8							0	0	0	0	0	0.01	
9	514	533	0	0 - 9	0 - 9	0 - 4							0	0	0	0	0	0.01	
10	533	567	0	0 - 10	0 - 3	0 - 4							0	0	0	0	0	0.01	
11	567	594	0	0 - 9	0 - 10	0 - 6							0	0	0	0	0	0.01	14 3/4" Surface Hole TD @ 594 mMDRT
12	594	594	0	0	0	0							0	0	0	0	0	0	
13	594	594	0	0	0	0							0	0	0	0	0	0	
14	594	594	0	0	0	0							0	0	0	0	0	0	
15	594	746	0.01 - 0.78	1 - 8700	0 - 983	0 - 322							0	0	0	0	0.795	1.52	
16	746	810	0.25	50 - 4786	12 - 1182	1 - 263	758.5	0.48					0	0	0	0.23	0.94	2.81	
	810	851	0.1																
	851	885	0.12																
	885	915	0.13				901.5	0.48											
	915	945	0.16				932.5	0.46											
	945	997	0.16																
17	997	1025	0.34	196 - 15675	63 - 7753	23 - 5172	1021	0.7					0	0	0	0.09	0.38	1.2	
	1025	1045	1.38				1031.5	2.06											
	1045	1065	3.59				1058	5.23											
	1065	1122	2.49				1067	4.78											
18	1122	1155	10.3	484 - 8673	165 - 3210	82 - 2274	1147.5	1.94					0	0	0	0.06	0.44	0.85	
	1155	1235	9.2				1168.5	0.77											
							1186	1.68											
	1235	1286	5.9				1240.5	1.83											
							1271.5	0.76											
							1296.5	1.65					0	0	0	0.15	0.36	0.5	9 7/8" Intermediate Hole TD @ 1308 mMDRT
							1298.5	1.88											
							1308	1.8											
19	1286	1308	1.04	650 - 5931	203 - 2636	107 - 1820													
20	1308	1308	0	0	0	0							0	0	0	0	0	0	
21	1308	1308	0	0	0	0							0	0	0	0	0	0	
22	1308	1335	0.8	1065 - 60760	432 - 22468	273 - 12569	1365	3.11					0	0	0	0	0.545	2.61	Carbide Lag check @ 1498m - Calculated Open hole size: 7.06% (2.2% Over gague)
	1335	1400	1.9																
	1400	1446	3																
	1446	1473	3.7																
	1473	1525	9.8				1480	8.72											
							1483	11.43											
23	1525	1525	0	0	0	0	0						0	0	0	0	0	0	
24	1525	1543	2	3341 - 27079	1293 - 7304	581 - 3847	1528	2.66			1525	4.69	0	0	0	0.18	0.335	0.59	
	1543	1563	1.5																
25	1563	1574	2.7	6657 - 30545	1904 - 5187	817 - 2083					1563	4.35	0	0	0	0.06	0.1	0.25	
26	1574	1671	2.77	4992 - 42330	1947 - 15820	731 - 7022	1701.5	9.29					0	0	0	0.5	0.16	0.26	
	1671	1747	5.32																
27	1747	1772	1.33	739 - 12223	320 - 4721	188 - 2573	1770	2.61					0	0	0	0.13	0.17	0.23	
	1772	1823	0.44																
28	1823	1861	0.22	325 - 2150	96 - 1054	50 - 754	1829	0.95					0	0	0	0.08	0.15	0.25	
29	1861	1887	0.21	461 - 1197	181 - 376	95 - 201	1868	0.33					0	0	0	0.13	0.37	1.62	
30	1887	1900	0.24	420 - 1059	166 - 422	84 - 241	1900	0.32					0	0	0	0	0.7	1.39	
31	1900	1900	0	0	0	0							0	0	0	0	0	0	
32	1900	1950.5	0.23	164 - 5838	38 - 1401	18 - 816	1915 1928.5 1942	0.44 0.29 0.25			1900	3.45	0	0	0	0	0.2	2	

