Overburde	en	Upper Sap	rolite	
OP	Pindan	С	Clay after basement lithology of indeterminate type	
OPG	Pindan with gravel – clast-supported	CSS	Sandy clay probably after sandstone	
DS .	Sand	CLST	Clay probably after limestone	
OSC	Sandy clay	CG	Basement sandy clay with gravel	
ocs	Clayey sand	CULM	Clay probably after magmatic lamproite	
OSCGR	Sandy clay with grit – matrix supported	CULT	Clay probably after tuffaceous lamproite	
OGR	Grit – clast-supported	CULTS	Clay probably after sandy tuffaceous lamproite	
OSG	Sand with gravel – matrix-supported	CUK	Clay probably after kimberlitic rock	
OSCG	Sandy clay with gravel – matrix-supported			
OCSG	Clayey sand with gravel – matrix-supported	Ultramafic Rocks		
OCG	Clay with gravel – matrix-supported	UK	Kimberlitic rock of indeterminate type	
OG	Gravel – clast-supported	UKB	Kimberlitic breccia	
OLGR	Transported lateritic grit			
OLG	Transported lateritic gravel	UL	Lamproitic rock of indeterminate type	
OGL	Lag gravel on bedrock surface	ULT	Lamproite tuff	
OSCL	Sandy clay with insitu laterite	ULTS	Sandy tuff (>20% quartz grains)	
OPWL	Pindan with weakly developed laterite	ULTR	Reworked tuff (clasts of tuff)	
OPML	Pindan with moderately developed laterite			
OPHL	Pindan with highly developed laterite	ULTL	Lapilli tuff Covetal right tuff (>20% opyetals)	
OSWL	Sand with weakly developed laterite	ULTX	Crystal-rich tuff (>20% crystals)	
	, ,	ULTW	Welded tuff	
OSML	Sand with moderately developed laterite	TS	Tuffaceous sandstone (>40% quartz grains)	
OSHL	Sand with highly developed laterite	ULBX	Lamproitic magmatic breccia, usually auto breccia	
OCWL	Clay with weakly developed laterite		T	
OCML	Clay with moderately developed laterite	-		
OCHL	Clay with highly developed laterite	4		
OB	Black soil	+ +		
		Chemical E	1	
Sediments		LNW	Weakly developed nodular laterite (overprinting plexisting rock)	
3	Sediment	LNM	Moderately developed nodular laterite	
SL	Limestone	LNH	Highly developed nodular laterite	
SST	Sandstone	LM	Massive laterite overprinting pre-existing rock	
SSS	Silicified sandstone	LL	Laminated laterite overprinting pre-existing rock	
SSF	Fine-grain sandstone	CCO	Chemical calcrete overprinting pre-existing rock	
SSM	Medium-grain sandstone	CCOW	Weakly developed calcrete overprint	
SSC	Coarse-grain sandstone	CCOH	Highly developed calcrete overprint	
SSFM	Fine to medium-grain sandstone	CCOM	Moderately developed calcrete overprint	
SSMC	Medium to coarse-grain sandstone	CSO	Chemical silcrete overprinting pre-existing rock	
SSFC	Fine to coarse-grain, poorly-sorted sandstone			
SGW	Greywacke - > 15% clay matrix, poorly sorted	Merlin-spe	Merlin-specific Rock Types	
SSL	Siltstone	Qsl	Quaternary soil	
SMD	Mudstone	Qfk	Ferricrete	
SCG	Conglomerate	Tlat	Tertiary laterite - insitu	
SBX	Breccia	Kslst	Cretaceous Siltstone	
SSH	Shale	Ksst	Cretaceous Sandstone Cretaceous Sandstone	
SSHC		Kb		
	Carbonaceous shale	1	Kimberlite Combridge Bulkelere Sendatone	
SCT	Chert	Ebsst	Cambrian Bukalara Sandstone	
		Pmd	Proterozoic (McArthur Group)	
		-	<u> </u>	
		-		

WET COLOUR DESCRIPTION			
Code	Intensity		
5	VERY DARK		
4	DARK		
3	MEDIUM		
2	LIGHT		
1	PALE		

Code	Colour	Code	Composite Colours
Gy	grey	GyWh	grey-white
Bu	blue	YeOr	yellow-orange
Pk	pink	OrYe	orange-yellow
Gn	green	YeGn	yellow-green
Kh	khaki	RdBn	red-brown
Ol	olive	OlGn	olive-green
Bl	black	BuGn	blue-green
Or	orange	CrWh	cream-white
Pu	purple	OrCr	orange-cream
Rd	red	RdBn	red-brown
Tn	tan	YeWh	yellow-white
Bn	brown		
Wh	white		
Ye	yellow		
Cr	cream		

WEATHERING/OXIDATION					
CODE	DESCRIPTION	DETAILED DESCRIPTION			
F	FRESH	ROCK SUBSTANCE UNAFFECTED BY WEATHERING, SULPHIDES OBSERVED.			
s	SLIGHTLY WEATHERED	ROCK SHOWS SLIGHT CHANGE OF COLOUR AND LUSTRE BUT GENERALLY SHOWS LITTLE OR NO CHANGE OF STRENGTH FROM FRESH ROCK.			
М	MODERATELY WEATHERED	SIGNIFICANT CHANGE OF COLOUR AND LUSTRE THROUGH THE ROCK FABRIC, AND ROCK STRENGTH IS NOTICEABLY REDUCED BY WEATHERING, BUT ROCK PIECES CANNOT BE BROKEN BY HAND ACROSS THE ROCK FABRIC AND THE ROCK MATERIAL IS NOT FRIABLE.			
Н	HIGHLY WEATHERED	ROCK STRENGTH AND HARDNESS CLEARLY REDUCED BY WEATHERING, ROCK PIECES CAN GENERALLY BE BROKEN BY HAND ACROSS THE ROCK FABRIC AD THE ROCK MATERIAL IS PARTLY FRIABLE; THE ROCK MAY BE HIGHLY DISCOLOURED, USUALLY BY IRONSTAINING.			
E	EXTREMELY WEATHERED	ROCK IS WEATHERED TO AN EXTENT THAT IT HAS SOIL PROPERTIES, IE. IN WATER IT EITHER DISINTEGRATES OR CAN BE REMOULDED, BUT ORIGINAL FABRIC IS MAINLY PRESERVED.			
R	RESIDUAL SOIL	ROCK IS COMPLETELY CHANGED TO SOIL IN WHICH ORIGINAL ROCK FABRIC IS COMPLETELY DESTROYED.			